Forklift Seat Belt

Seat Belts for Forklift - Described in the Regulation guidelines are the application of seatbelts and operator restraints on lift trucks. It states that the liability falls on the employers' to be able to make sure that each machine, piece of equipment and tool is used rightly utilized in accordance to the directions of the producer.

Rough Terrain forklifts have to meet the guidelines of ANSI Standard ASME B56.6-1992 regarding their inspection, fabrication, use, design and maintenance.

Side boom tractors and mobile equipment with a Rollover Protective Structure, or ROPS for short, should include seat belts which meet the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whatever mobile equipment has seat belts required by law, the operator and subsequent passengers ought to ensure they make use of the belts whenever the motor vehicle is in motion or engaged in operation for the reason that this could cause the machinery to become unstable and hence, unsafe.

If a seat belt or different operator restraint is needed on a lift truck.

The seat belt requirements while working a forklift depend on various factors. Whether or not the lift truck is outfitted with a Rollover Protective Structure, the type of lift truck itself and the year the forklift was made all add to this determination. The manufacturer's directions and the requirements of the applicable standard are referenced in the Regulation.

With regards to powered industrial trucks, ANSI Standard ASME B56.1-1993 refers to an operator restraint device, system, or enclosure. A driver restraint device, enclosure or system is designed so as to help the driver in lessening the danger of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The system or restraint device may include a seat belt, even if a seat belt is not necessarily a part of such device or system.